



BELT-DRIVE COMPRESSOR 50L

VICOC50

With a working pressure of 8 bar (115 psi) is the ideal choice for the most demanding jobs, anything from industrial use to work in repair shops and construction sites. With a 50-litre tank capacity, it allows for greater autonomy, reducing the need for frequent stops to recharge. In addition, the maximum air flow rate of 233 L/min ensures a constant and efficient air flow, ideal for pneumatic tools and other applications that require a continuous supply of compressed air. With an air filter and an IP20 rating, it provides basic protection for internal components and improves the quality of the compressed air, reducing maintenance and increasing overall equipment effectiveness in controlled environments.

Key features

- > 50 litres capacity;
- > Maximum air flow rate of 233 L/min;
- > Belt drive transmission system 1400rpm (increased durability);
- > Constant and efficient airflow;
- > Air filter;
- > IP20 rating, to carry out all tasks safely;
- > Greater power, durability, and less vibration.



Specifications

Engine oil	15W-40
Height	690 mm
IP code	IP20
Length	940 mm
Maximum flow rate	233 L/min
No-load Speed	2850 rpm
Oil crankcase capacity	326 ml
On/off switch	Yes
Operating pressure	8 bar / 115 psi
Product weight	51.086 kg
Rated power	2,5 cv / 1,9 kW
Rotation speed	1350 rpm
Safety valve	Yes
Sound power level (LWA)	95 dB(A), k = 3
Tank capacity	50 L
Tank top outlet for fixed network connection	Yes
Thermal protection	Yes
Weight with packaging	54.125 kg
Width	380 mm

Package Contents

Included accessories: - Wheels

- Air filter.