



## DIESEL TILLER WITH DIRECT TRANSMISSION - 7HP

### VIMEDTD7A

Diesel powered tiller with a power of 7 hp and a displacement of 246cc. The tiller has a 3-speed engine with 3600 rpm, a 3.6L fuel tank, a 600ml oil tank, 115cm tines, a cutting diameter of 35cm. It also includes a carrying handle and a battery.

#### Key features

- > High quality 7hp diesel tiller with direct transmission. - Excellent performance, satisfies even the most demanding needs. - Displacement of 246 CC.



#### Specifications

|                            |                              |
|----------------------------|------------------------------|
| Assembly                   | <b>Not Assembled</b>         |
| Battery for electric start | <b>Yes</b>                   |
| Dimension                  | <b>670 x 1300 x 1130 mm</b>  |
| Engine                     | <b>4-ST combustion</b>       |
| Engine displacement        | <b>246 CC</b>                |
| Engine oil                 | <b>15W40</b>                 |
| Engine oil crankcase       | <b>0,6 L</b>                 |
| Fuel                       | <b>Diesel</b>                |
| Fuel tank capacity         | <b>3,6 L</b>                 |
| Gear oil                   | <b>2 L</b>                   |
| Gearbox oil                | <b>80W90</b>                 |
| Packaging dimensions       | <b>880 x 455 x 815 mm</b>    |
| Power                      | <b>7 cv / 5,2 kW</b>         |
| Product weight             | <b>117 Kg</b>                |
| Rotation speed             | <b>3600 rpm</b>              |
| Sound power level (LWA)    | <b>98dB</b>                  |
| Speeds                     | <b>2 forward + 1 reverse</b> |
| Tine diameter              | <b>350 mm</b>                |
| Transmission               | <b>Direct</b>                |
| Weight with packaging      | <b>127 Kg</b>                |
| Working width              | <b>1150 mm</b>               |

Variants

#### Package Contents

- Fresas para motoenxada
- Regulador de profundidad.



| Reference   | Assembly         | Battery<br>For<br>Electric<br>Start | Dimension               | Engine             | Engine<br>Displacement | Engine<br>Oil | Engine Oil<br>Crankcase | Fuel   | Fuel<br>Tank<br>Capacity | Gear<br>Oil | Gearbox<br>Oil | Packaging<br>Dimensions | Power            | Product<br>Weight | Rotation<br>Speed | Sound<br>Power<br>Level<br>(Lwa) | Speeds                         | Tine<br>Diameter | Transmission | Weight<br>With<br>Packaging | Working<br>Width |
|-------------|------------------|-------------------------------------|-------------------------|--------------------|------------------------|---------------|-------------------------|--------|--------------------------|-------------|----------------|-------------------------|------------------|-------------------|-------------------|----------------------------------|--------------------------------|------------------|--------------|-----------------------------|------------------|
| VIMEDTD7A   | not<br>assembled | yes                                 | 670 x 1300<br>x 1130 mm | 4-st<br>combustion | 246 cc                 | 15w40         | 0,6 l                   | diesel | 3,6 l                    | 2 l         | 80w90          | 880 x 455 x<br>815 mm   | 7 cv /<br>5,2 kw | 117 kg            | 3600<br>rpm       | 98db                             | 2<br>forward<br>+ 1<br>reverse | 350 mm           | direct       | 127 kg                      | 1150<br>mm       |
| VIMEDTD7A.M | assembled        | yes                                 | 670 x 1300<br>x 1130 mm | 4-st<br>combustion | 246 cc                 | 15w40         | 0,6 l                   | diesel | 3,6 l                    | 2 l         | 80w90          | 880 x 455 x<br>815 mm   | 7 cv /<br>5,2 kw | 117 kg            | 3600<br>rpm       | 98db                             | 2<br>forward<br>+ 1<br>reverse | 350 mm           | direct       | 127 kg                      | 1150<br>mm       |