



DIESEL TILLER WITH DIRECT TRANSMISSION - 7HP

VIMEDTD7B

Direct-transmission Diesel Tiller - 7CV from VITO (VIMEDTD7B). With a 246cc diesel engine and 7hp/5.2 kW, it's perfect for small to medium-sized plots. Electric start provides convenience at the beginning of operations, while triple filtration and the oil sensor ensure durability and consistent engine performance. The 3-speed gearbox (2 forward + 1 reverse) offers versatility to adapt to different soil conditions and tasks. The 35cm diameter cultivators and furrow opener ensure precise and efficient work. Additionally, the quick adjustment of the front rest makes handling more practical and comfortable. Get ready to tackle any challenge on your land with the confidence and performance of VITO's Direct-transmission Diesel Tiller.

Key features

- > Electric start;
- > Triple filter system;
- > Oil level sensor;
- > Front stand.



Specifications

Battery for electric start	Yes
Dimensions	670 x 1300 x 1130 mm
Engine	4-ST combustion
Engine displacement	246 CC
Engine oil	15W40
Engine oil crankcase	0,6 L
Fuel	Diesel
Fuel tank capacity	3,6 L
Gear oil	2 L
Gearbox oil	80W90
Packaging dimensions	880 x 455 x 815 mm
Product weight	117 Kg
Rated power	7 cv / 5,2 kW
Rotation speed	3600 rpm
Sound power level (LWA)	98dB
Speeds	2 forward + 1 reverse
Tine diameter	350 mm
Transmission	Direct
Weight with packaging	127 Kg
Working width	1150 mm

Variants																				
Reference	Battery For Electric Start	Dimensions	Engine	Engine Displacement	Engine Oil	Engine Oil Crankcase	Fuel	Fuel Tank Capacity	Gear Oil	Gearbox Oil	Packaging Dimensions	Product Weight	Rated Power	Rotation Speed	Sound Power Level (Lwa)	Speeds	Tine Diameter	Transmission	Weight With Packaging	Working Width
VIMEDTD7B	yes	670 x 1300 x 1130 mm	4-st combustion	246 cc	15w40	0,6 l	diesel	3,6 l	2 l	80w90	880 x 455 x 815 mm	117 kg	7 cv / 5,2 kw	3600 rpm	98db	2 forward + 1 reverse	350 mm	direct	127 kg	1150 mm

VIMEDTD7B.M	yes	670 x 1300 x 1130 mm	4-st combustion	246 cc	15w40	0,6 l	diesel	3,6 l	2 l	80w90	880 x 455 x 815 mm	117 kg	7 cv / 5,2 kw	3600 rpm	98db	² forward + 1 reverse	350 mm	direct	127 kg	1150 mm
-------------	-----	-------------------------	--------------------	--------	-------	-------	--------	-------	-----	-------	-----------------------	--------	------------------	-------------	------	---	--------	--------	--------	------------