







This table saw, with a no-load speed of 5000 rpm, a 24-tooth blade, 2.8 mm thickness, a 250 mm blade diameter, and a 30 mm blade hole diameter, allows you to perform various cuts with magnificent results in an optimized and safe manner. The table is equipped with a rip fence for perfectly precise longitudinal cuts and a mitre gauge for mitre cuts. Thanks to these features, the workpieces are always at the same distance from the blade, allowing for exact cuts. The table is ideal for performing bevel cuts with a maximum depth of up to 85 mm and a mitre angle of 0° to 45°. It also includes table extensions for wider workpieces and stabiliser bars to ensure maximum comfort while working. The appliance contains a hex key, making it simple and safe to change the blade, and it features a push stick to keep fingers out of harm's way. This table saw has the clear advantage of an adapter and a hose to vacuum up dust and chips, protecting the user and providing a clean working environment. It stands out for its versatility and ease of transport to any location, ensuring maximum stability of the machine through its sturdy structure with a metal base.







## **Key features**

- > Bevel cut (0º to 45º);
- > Hose for dust and shavings suction;
- > Auxiliary Table 640 x 200 mm.

## **Specifications**

-	
(Bevel) Max. width x cutting depth 45°/0°	85 mm
(Bevel) Max. width x cutting depth 45°/45°	65 mm
(Miter) Max. width x cutting depth 0°/0°	85 mm
(Miter) Max. width x cutting depth 0°/45°	65 mm
Blade diameter	250 mm
Blade hole diameter	30 mm
Cutting angle (bevel)	0º / 45º
Cutting angle (miter)	- 60º / 0º / + 60º
Disc thickness	2,8 mm
Height	330 mm
Length	740 mm
Miter gauge	Yes
No-load Speed	5000 rpm
Number of teeth on the blade	24
Parallel guide	Yes
Product weight	20.251 kg
Rated power	1800 W
Sound power level (LWA)	104 dB(A), k = 3
Stable legs	Yes
Weight with packaging	22.501 kg
Width	620 mm

November 01, 2025, 18:25h Page 1 of 1 vito-tools.com